EXPLORER 3075

0.75 Meter, Multi-Band Manual Fly-Away Antenna System



February 2015 Product Sheet

The most important thing we build is trust



EXPLORER 3075

This 3-axis Manual Fly-Away system provides users with a lightweight, ruggedized, and modular mobile terminal capable of X, Ku and Ka-band operation. Its ease of use allows for operators with minimal satellite experience to access any broadband application within ten minutes.

System Features

- Modular design allows easily field-changable feed/RF chain
- Multiple bands and G/T & EIRP levels
- Transport: One-Man Carry
- Rugged, lightweight

Network configurations also exist for Eutelsat (KA-SAT), Avanti, and Hylas.

Markets

- Military
- Homeland Security
- Emergency Response
- Law Enforcement
- Media: Live Streaming Video, TV Broadcasting
- Telemedicine: Critical Medical Information Transmission
- Mobile Insurance Claims & Settlements
- Remote Office Communications
- Energy and Mining

Applications

- Continuity of Business Operations
- Remote Business Videoconferencing
- Internet Cloud Services: Voice, Radio, Data, Fax, Live Broadcast
- **Assembly Time**

Approximately 10 Minutes (typical)

Reflector

Size	75 cm Carbon Fiber Reinforced Polymer (CFRP)
Optics	Axis-Symmetric Stepped Ring Focus
Construction	Multi-Segment, Multi-band shaped parabolic
Polarization	2 Port Circular / Linear - Band Dependent

Mechanical

Axis Drive System	3-Axis Positioner (manual point)
Mount Geometry	Elevation over Azimuth
Travel Azimuth Elevation Polarization	±15° Fine-Tuning 0° to 85° ±90° Manual Linear Adjustment RH / LH Circular Selection

Weights & Measures

Antenna*	12 kg (26.5 lbs)
	(for Ku-band configuration with 8W BUC and LNB)
Antenna with	18.5 kg (40 lbs)
Soft BackPack	
Hardcase	29 kg (64 lbs)
containing Antenna	Shipping Dimensions:
and Soft BackPack	86.4 L x 61 W x 51 H cm (34" x 24" x 20")
	Airline checkable (IATA-compliant)

*Dependent on BUC/LNB configuration Specifications Subject to Change Without Notice.

EXPLORER 3075



0.75 Meter, Multi-Band Fly-Away Antenna System

Antenna Characteristics		Ka-Band Military	Ka-Band Commercial	Ka-Band KA-SAT (Eutelsat)	Ku-Band	X-Band*
Feed		2 Port Circular			2 Port Linear	2 Port Circular
Frequency (GHz)	Rx	20.2 - 21.2	19.2 - 20.2	19.7 - 20.2	10.95 - 12.75	7.25 - 7.75
	Tx	30.0 - 31.0	29 - 30	29.5 - 30	13.75 - 14.5	7.90 - 8.40
Gain (dBi ± 0.2)	Rx	41.5	41.0	41.0	36.9	33
	Tx	44.7	45.5	45.5	38.5	33.7
Cross Pol Isolation (CP) / Axial Ratio (AR) (dB)	Rx	1.5 (AR)	1.5 (AR)	1.5 (AR)	30 (CP)	2.0 (AR)
	Tx	1.0 (AR)	1.5 (AR)	1.5 (AR)	30 (CP)	2.0 (AR)
G/T - Comm @ 30° EL, Midband (dB/°K)		17.3	17.0	17.0	15.7	11.5
Standard BUC options (Watts)		5	5	4	8 / 16	10 / 20
System EIRP (dBW)		51.5	51.3	50	47.5 / 50.5	43.7 / 46.7

Environmental

Wind Speed - Operational	40 km/h (25 mph) (not anchored) 48 km/h (30 mph), gusts up to 72 km/h (45 mph) (anchored)		
Temperature - Operational	-25° to +55°C (-13° to +131°F)		
- Survival	-40° to +80°C (-40° to +176°F)		
Rain	<100 mm/hr		
Humidity	0 to 100% (condensing)		

* Military X-band available







Backpack Inside Hard Case

Backpack

About EXPLORER Products

Cobham SATCOM Land offers a diverse array of turn-key satellite terminals that fulfill critical communications needs and reduce system configuration requirements for end users. The solutions we provide offer a wide variety of data rates in multiple frequency bands including L, Ku, Ka, and X-bands. Systems are available as manual, or auto-deploy configuration, and are organized in drive-away, fly-away and comm-on-the-move (COTM) families. When traditional communication technologies are unavailable or fail, our products provide high quality VoIP, RoIP, FAX, data, and multimedia communications that work efficiently across satellite links. We specialize in assisting partners with integrated end-to-end solutions for rapid deployment to support disaster recovery, continuity of operations and other mission critical applications.



Inside Backpack Subject to change without further notice.



For further information please contact:

Cobham SATCOM Land 2100 N Alafaya Trail Suite 300 Orlando, Florida 32826 USA Tel: + 1-407-650-9054 Fax: + 1-407-650-9086